
PRODUCT DATA SHEET

2102 - D/S Mirror Mounting Foam Tape

Description

A double sided foam tape with a solvent acrylic adhesive, a white closed cell polyethylene foam carrier and a white siliconized paper liner
The tape excels by its combination of a very high adhesion to polar and a-polar surfaces, a high tack and an extremely high shear at ambient temperature conditions

Application

Mounting of mirrors, plinths, decorative trims, household utilities, etc

Characteristics

Carrier	:	White polyethylene foam
	100 kg/m ³	0.8mm
Liner	:	Siliconized paper 70µm
Adhesive	:	Solvent Acrylic
Total thickness, without liner (µm)	:	900
90° Adhesion to PE at RT (N/25mm)	:	9.0
Holding power > 168h at RT (kg)	:	3
Tensile strength (N/25mm)	:	45
Temperature range (°C)	:	-20 to +70

Available Sizes

Width (mm)	:	Upon request
Length (mm)	:	Upon request
Core (mm)	:	Upon request

Conditions

Store in a cool dry place away from sunlight heat sources
As far as the storage conditions are respected, the product is guaranteed 12 months

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.